

TBM-1222

Tiny-Bus 4-Channel 120fps Video Capture Module with 4-Channel 120fps Video Capture BNC and Mini-PCI Type-III A/B Socket



Key Features

The TBM-1222 is a Tiny-Bus[®] video capture module with onboard four PCI-based BT878A controllers with 120 fps of video capture capacity for the DVR surveillance and other small form factor (SFF) industrial x86-based computing applications.

- Onboard four BT878A controllers with up to 120 frame per second of video capture capacity.
- Four BNC video input interfaces.
- One mini-PCI type-III A/B socket.
- Liantec embedded Tiny-Bus[®] Modular Expansion Solution.

Specification

Tiny-Bus[®] Modular Expansion Solution with PCI-based bus interface
Onboard four BT878A video capture controller supports 120 fps MAX
 Onboard Type-III A/B mini-PCI socket

External / Internal Connector

External four BNC connectors
 Onboard 124-pin mini-PCI Type-III socket

Compatible EmBoard

ITX-6965	Mini-ITX Intel Mobile 965 Express EmBoard
ITX-6945	Mini-ITX Intel Mobile 945 Express EmBoard
ITX-6910	Mini-ITX Intel Mobile 915 Express EmBoard
ITX-6900	Mini-ITX Intel Mobile 915 Express EmBoard
ITX-6815	Mini-ITX Intel Pentium M / Celeron M EmBoard
ITX-6810	Mini-ITX Intel Pentium M / Celeron M EmBoard
ITX-6800	Mini-ITX Intel Pentium M / Celeron M EmBoard
ITX-6700	Mini-ITX AMD Embedded Geode NX EmBoard
EMB-5740	5.25" Drive-size VIA C7-Eden Multi-Ethernet EmBoard
EMB-3700	3.5" Drive-size VIA C7-Eden Multimedia EmBoard

Ordering Code

TBM-1222B4P	Tiny-Bus 4-CH Video Capture and Mini-PCI Module with Four BT878A Video Capture Controller
--------------------	---

Mechanical Drawing

